



**Produkts ražots Vācijā!**  
Importētājs: SIA "Abschliff Latvija"  
Rīga, A Čaka iela 107 K2  
Tālrunis: +371 67843844, 67843845  
Fakss: +371 67272792  
Mob.: +371 26177888  
E-pasts: [abschliff.latvija@gmail.com](mailto:abschliff.latvija@gmail.com)  
[www.abschliff.lv](http://www.abschliff.lv)  
<https://www.facebook.com/abschliff.abschliff>



**Veikala darba laiks: darba dienās – 9<sup>00</sup>-18<sup>00</sup>, sestdienās - 10<sup>00</sup>-14<sup>00</sup>, svētdienās – brīvs**

## Brilliance Cleaner L94 - cleaner/wax remover

### Description

Basic cleaner removing dirty films of self-shining maintenance products resp. wax coats on finished hardwood and other wooden floors. Basic cleaning is necessary whenever maintenance films have taken up too much dirt and the floor has become unsightly.

Giscode: GU50

### Note!

Do not soak the floor with water, otherwise the wood may be damaged by swelling. If Brilliance Cleaner L94 is left on the floor for too long, the finishing film may be damaged. If a floor is damaged or the finishing film is worn through to the wood, penetrating water may have a greying effect on the wood. In this case the floor should be sanded completely and refinished in due time.

### Application

Brilliance Cleaner L94 can be used both for basic cleaning and (strongly diluted with water) for intermediate cleaning.

**Basic cleaning for sealed surfaces:** the floor is moistened. Brilliance Cleaner L94 is spread and scrubbed after a short waiting period either manually or by means of a machine. Depending on the extent of the soiling and the thickness of the film, Brilliance Cleaner L94 is either used undiluted or mixed with water (mixing rate 1:1). If necessary, the cleaning procedure is repeated. The solved dirty film is removed and the floor is wiped with clear water.

**Intermediate cleaning for sealed and oiled surfaces:** necessary if the surface is slightly dirty only. Approx. 300 ml of Brilliance Cleaner L94 is added to 10 l of water and the superficial dirt is removed by normal wet-cleaning.

**Intensive cleaning for oiled surfaces:** the floor is moistened. Brilliance Cleaner L94 is spread out and scrubbed manually or mechanically after a short exposure. Depending on the degree of soiling and the thickness of the care film, apply pure or 1: 1 diluted with water and repeat the cleaning process if necessary. The loosened dirt film must be taken up immediately. Afterwards, always wipe with clear water. After this intensive cleaning, further treatment with Classic BaseOil, Brilliance Fitpolish, Brilliance OilCare, Classic 100ProOil or Brilliance Superwax may be necessary. For a thorough cleaning with oil removal, we recommend Brilliance BioSoap or Brilliance Cleaner L91.

### Consumption

Approx. 20 ml/m<sup>2</sup> or 50 m<sup>2</sup>/l

### Storage / transport

Shelf life of original unopened packing 24 months min. provided that material is transported and stored at a cool and dry place.

**Packaging:** 1 l, 5 l.

**Attention!** Even when working with materials that contain a small amount of harmful substances, it is necessary to follow the generally accepted labor protection regulations. Keep the product out of the reach of children.

