



Made in Germany!
Importer: Ltd "Abschliff Latvija"
Rīga, A Čaka iela 107 K2
Phone: +371 67843844, 67843845
Fakss: +371 67272792
Mob.: +371 26177888
E-mail: info@abschliff.lv
www.abschliff.lv

<https://www.facebook.com/Abschliff-Latvija-100679528475676/>



Open: Monday to Friday – 9⁰⁰-18⁰⁰, Saturday- 10⁰⁰-14⁰⁰, Sunday – closed

Avalon Steinol - oil for stone surfaces

Description

For indoor impregnation and maintenance of all absorbent tiles and concrete surfaces, such as B. terracotta, etc. Protects against general contamination, grease and oil. Suitable as a joint protection for cement joints. Water repellent and wear-resistant, does not burn the surface noticeably.

GISCODE: Ö 60+

Colour

Colorless

Ingredients

Sunflower oil boiling, natural resin esters, isoparaffins, drying agents. The VOC content of this product is max. 520 g / l. The EU limit value is a maximum of 700 g / l (category f from 2010).

Application

Stir well before use. The surface must be dry, clean and free of grease and dust. Apply rock oil with a brush or roller. After a penetration time of about 20-30 minutes, the excess oil is squeezed out or removed from the areas that are still absorbent, and the surface is dried with a dry cloth or pad. The next day, reapply the plan and process as described above. Depending on the absorbency of the substrate, apply a third coat.

Important: there must be no layer of oil on the surface!

Drying time

Dry and recoatable after 4 - 6 hours (18 - 22 ° C / 50 - 55% relative humidity). Complete drying takes approx. 7-10 days

Packaging and consumption

Approx. 20 - 50 ml / m² depending on the absorbency of the substrate.

Packaging: 0,75 l for 21,5 m²; 2,5 l for 71,5 m²

Storage

Store in a cool, tightly closed place. If skin forms, remove before re-use. If necessary, strain the oil.

Disposal

According to local, official regulations. Dried product residues can be disposed of with household waste. Waste code: EAK / EWC 08 01 11

Dilution and instrument cleaning

Cleaning with pH neutral detergent in lukewarm water.

Precautionary statements

Keep out of the reach of children. Ingestion: Immediately call a POISON CENTER / doctor. DO NOT induce vomiting. Avoid release to the environment. Dispose of contents / container for proper recycling.

Working materials impregnated with the product, such as rags, sponges, etc. place in hermetically sealed metal containers or water and then dispose of them, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The product itself is not self-igniting. Adequate ventilation must be provided during drying. Due to the natural raw materials used, a typical odor may occur. Wear approved respiratory protection when using spray equipment. Wear a fine dust mask when sanding!

Safety data sheet available on request.

