



Made in Germany!
Importer: Ltd "Abschliff Latvija"
Riga, A Čaka iela 107 K2
Phone: +371 67843844, 67843845
Fakss: +371 67272792
Mob.: +371 26177888
E-mail: info@abschliff.lv
www.abschliff.lv



<https://www.facebook.com/Abschliff-Latvija-100679528475676/>

Open: Monday to Friday – 9⁰⁰-18⁰⁰, Saturday- 10⁰⁰-14⁰⁰, Sunday – closed

Brilliance Fitpolish - care and restoration wax

Description: Brilliance Fitpolish is a clear solvent-based cleaning and maintenance product containing natural additives for finished, oiled and waxed hardwood floors as well as for other solvent- resistant substrates (stone, plastic etc.). This product containing wax has excellent care properties and requires buffing after application. Giscode GH10

Application: shake well before use. Carefully clean the surface to be treated prior to application. Hardwood floors in particular must be cleaned with a mop, broom, vacuum cleaner or with a damp cloth. Heels marks and stains are removed punctually using Brilliance Fitpolish and a soft cloth. Do not use any steel wool, steel shavings or screening pads. In addition, the floor temperature during application must be 15°C min. in order to avoid crystallization of the wax and formation of white spots. Thickened Brilliance Fitpolish can be liquefied in a water-bath (max. 50°C).

Basic maintenance: for basic maintenance of large areas, a thin and uniform layer of Brilliance Fitpolish is applied with a soft and clean cloth or sponge (either manually or by means of a machine) and buffed after drying. For basic cleaning and removal of the dirty wax film, Brilliance Cleaner L91 KH-Verdünnung (solvent-based thinner) is used. Afterwards, the surface is treated with Brilliance Fitpolish again.

Important advice: due to the high wax content, floors treated with Brilliance Fitpolish are rather slippery. This can be either be a desired effect or tolerated by the user. In some cases, slippery floors are not acceptable, for example, for especially endangered persons or in most public buildings. For these purposes we recommend our antiskid water-based maintenance product Brilliance Everclear provided that the floor has not only an impregnation but an intact finishing coat.

Consumption: depending on substrate and application method approx. 7-13 ml/m² resp. approx. 75-150 m²/l.

Storage/transport: shelf life of original unopened packing 24 months min. provided that material is transported and stored at a cool and dry place protected from freezing.

Packaging: 1 l, 5 l.

Attention! Even when working with materials that contain a small amount of harmful substances, it is necessary to follow the generally accepted labor protection regulations. Keep the product out of the reach of children.

